

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 913 123 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
06.05.1999 Bulletin 1999/18

(51) Int Cl.<sup>6</sup>: **A61B 17/064**

(21) Application number: **98890309.2**

(22) Date of filing: **21.10.1998**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Grafton, Donald R.**  
Naples, FL 33963 (US)  
• **Brunsvold, Mark**  
Naples, FL 34116 (US)

(30) Priority: **29.10.1997 US 63445 P**  
**19.06.1998 US 99869**


(74) Representative: **Kopecky, Helmut, Dipl.-Ing.**  
**Kopecky & Schwarz Patentanwälte et al**  
**Wipplingerstrasse 32/22**  
**1010 Wien (AT)**

(71) Applicant: **Arthrex Inc**  
**Naples, Florida 34104 (US)**

(54) **Meniscal repair device**

(57) A meniscal tissue repair device includes an elongate body having a pointed distal tip. A plurality of lateral grooves is disposed along the body. Grooves disposed near the distal tip of the device are angled to open proximally and grooves disposed near the proximal end are angled to open distally. A torn meniscus can be repaired using the meniscal repair device by loading the

meniscal repair device into an applicator, and inserting the barrel of the applicator through an incision in the knee at a location proximal and perpendicular to the tear in the meniscus. The applicator is actuated to drive the repair device distally into the meniscus across the tear. The distal travel of the repair device is limited by the distally-opening grooves of the repair device.



**FIG. 2**

**EP 0 913 123 A1**

## Description

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention:

[0001] The present invention relates to surgical methods and apparatus for repair of meniscal tears.

#### 2. Description of the Related Art:

[0002] The menisci are crescent-shaped structures of fibrocartilaginous tissue located in the knee between the condyles of the tibia and the femur. The menisci, which are actually extensions of the tibia, serve to deepen the tibial plateau to better accommodate the opposing curvature of the articulating surface of the femoral condyle.

[0003] A typical injury to the knee is a meniscal tear, which can occur, for example, when the meniscus is displaced and caught between the femoral and tibial condyles during a sudden change of movement of the knee involving a combined flexion-rotation or extension-rotation motion. Meniscal tears were originally treated by removing the meniscus in an operation called a meniscectomy. However, results showed that removing the meniscus, either entirely or even partially, resulted in degenerative arthritis and instability in the knee.

[0004] As a result of the above-described complications, surgeons began treating torn meniscus tears with suturing techniques to retain as much of the meniscus as possible. However, suturing of a meniscal tear, like a meniscectomy, was originally an open technique, requiring a large incision and consequently longer periods of rehabilitation and recovery. Advances in instrumentation ultimately led to arthroscopic meniscal repair using long needles for passing suture through the tear.

[0005] More recently, various tacks and screws have been developed for meniscal repair, which can be used arthroscopically and simplify the surgery by eliminating the need for suturing altogether. See, for example, U.S. Pat. Nos. 4,873,976; 4,884,572; 4,895,148; 4,924,865; 4,976,715; 5,059,206; 5,129,906; 5,562,672; and 5,569,252. The known tacks and associated surgical methods have various disadvantages, such as the need for special preparation of the meniscus prior to insertion.

### SUMMARY OF THE INVENTION

[0006] The present invention provides an improved meniscal repair device which, when used in conjunction with a specially-designed insertion gun, provides a simplified, quick and accurate method for repairing a torn meniscus.

[0007] Briefly, the meniscal repair device of the present invention has a pointed distal tip, a proximal end, and a cylindrical body provided with a plurality of crescent-shaped grooves. The grooves on the front end of device face proximally and are disposed on opposite

sides of the device in alternating fashion. The grooves on the proximal end of the device face distally.

[0008] To insert the device into a torn meniscus, the device is first loaded into the elongated barrel of a spring loaded applicator, such that the back end of the device mates with the tip of the plunger of the applicator. The barrel of the applicator is then inserted through an incision in the knee and located arthroscopically at a location proximal and perpendicular to the tear in the meniscus. The trigger of the applicator is then actuated, releasing the plunger in the barrel, and driving the repair device distally into the meniscus across the tear. The distally facing grooves on the proximal end of the repair device limit forward motion of the device into the meniscus. Advantageously, the repair device of the present invention preferably is formed of a bioabsorbable material such as PLLA.

[0009] The device and method of the present invention can be used not only to repair meniscal tears as described herein, but can also be used to repair any bodily tissue, such as cartilage, bone, skin and ligaments.

[0010] Other features and advantages of the present invention will become apparent from the following description of the invention which refers to the accompanying drawings.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Fig. 1 is a side view of the repair device of the present invention.

[0012] Fig. 2 is a top view of the repair device of the present invention.

[0013] Fig. 3 is a proximal end view of the repair device of the present invention.

[0014] Fig. 4 is a side view of the applicator used to insert the repair device in the method of the present invention.

[0015] Fig. 5 is a top view of the applicator used to insert the repair device in the method of the present invention.

[0016] Fig. 6 is a perspective view of the applicator used to insert the repair device in the method of the present invention.

[0017] Fig. 7 is a schematic representation of a tissue repair using the repair device of the present invention.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0018] Referring first to Figs. 1-3, the present invention comprises a meniscal repair device 2 which has a pointed trocar tip 4 on the distal end, a rounded proximal end 6, and a cylindrical body 8. Along the body 8 is a plurality of lateral, crescent-shaped grooves 10, 12, disposed on opposite sides of the device in alternating fashion.

[0019] The grooves are formed at an angle of about

30° to the axis of the body 8. Grooves 10 on the distal end of device 2 open proximally. Grooves 12 on the proximal end of the device open distally. The base of each groove typically is rounded. The surfaces of adjacent grooves 10, 12 on each side of the body 8 converge at an acute angle to form edges that anchor against the meniscal tissue.

[0020] The grooves are spaced equally at either end of the body 8, with the pattern of grooves on one side of the device being offset by about half the distance between grooves on the other side of the device.

[0021] The devices are provided in various lengths of 10 mm, 12 mm, and 14 mm. A device 2 of proper length is selected such that the inserted device does not protrude through the joint capsule.

[0022] To insert device 2 into a torn meniscus, the device is first loaded into the elongated barrel of a spring loaded applicator 14, shown in Figs. 4-6. Applicator 14 has a structure similar in certain respects to that disclosed in U.S. Patent No. 5,546,957, the entire disclosure of which is incorporated herein by reference. Applicator 14 has a spring-loaded plunger 16 that slides within a barrel 18. After the plunger of applicator 14 has been retracted by pulling rearwardly on knob 20, repair device 2 is loaded, proximal end first into applicator 14, such that proximal end 6 of device 2 mates with the tip of plunger 16 of applicator 14.

[0023] After applicator 14 has been loaded with a repair device 2, applicator 14 is grasped by a handle 22 and inserted through an incision in the knee, and the tip 23 of barrel 18 is located arthroscopically at a location proximal and perpendicular to the tear in the meniscus. After a safety on the applicator 14 has been switched off, trigger 26 of the applicator is actuated by the surgeon, releasing plunger 16 to move forcefully forwardly in barrel 18 under the force of spring 28, driving the repair device out of barrel 18 and distally into the meniscus across the tear. Protruding portions of the repair device can be cut off, through small separate incisions, if necessary. Advantageously, the repair device of the present invention is preferably formed of a bioabsorbable material such as PLLA.

[0024] Referring to Fig. 7, three repair devices 30, 32, and 34 according to the present invention are shown having been inserted into tissue 36 to approximate a tear 38. The proximally-facing grooves of the repair devices limit the rearward motion. The distally-facing grooves limit the forward motion of the devices, and prevent over-insertion.

[0025] The device and method of the present invention can be used not only to repair meniscal tears as described herein, but can also be used to repair any bodily tissue, such as cartilage, bone, skin and ligaments.

[0026] Although the present invention has been described in relation to particular embodiments thereof, many other variations and modifications and other uses will become apparent to those skilled in the art. There-

fore, the present invention is to be limited not by the specific disclosure herein, but only by the appended claims.

## Claims

1. A tissue repair device comprising an elongate body having a pointed distal tip, a proximal end, and a plurality of lateral grooves disposed along the body, wherein grooves disposed near the distal tip of the device are angled to open proximally and grooves disposed near the proximal end are angled to open distally.
2. The tissue repair device of claim 1, wherein the elongate body has opposing sides, and the grooves are disposed on opposite sides of the body.
3. The tissue repair device of claim 2, wherein the grooves form a regular pattern, the pattern on one side of the elongate body being offset from the pattern on the opposite side of the body.
4. The tissue repair device of claim 1, wherein the elongate body has an outer circumference which is substantially constant along the length of the body proximal to the distal tip, and the proximal end has a circumference which is substantially equal to the outer circumference of the elongate body.
5. A meniscal repair device comprising:
  - means for insertion within tissue and having a proximal section and a distal section;
  - means for engaging tissue and limiting distal movement of the device within the tissue disposed along the proximal section; and
  - means for engaging tissue and limiting proximal movement of the device within the tissue disposed along the distal section.
6. A method of repairing a torn meniscus using a meniscal repair device comprising an elongate body having a distal tip, a proximal end, and a plurality of grooves disposed along the body, wherein grooves disposed along the body near the distal tip of the device open proximally and grooves disposed along the body near the proximal end open distally, the method comprising the steps of:

- loading the meniscal repair device into an applicator;
- inserting a barrel of the applicator through an incision in the knee at a location proximal and perpendicular to the tear in the meniscus; and
- actuating the applicator to drive the repair device distally into the meniscus across the tear, the distal travel of the repair device being limit-

ed by the distally opening grooves of the repair device.

5

10

15

20

25

30

35

40

45

50

55

4




FIG. 1




FIG. 2




FIG. 3




FIG. 7




FIG. 5




FIG. 4




FIG. 6





European Patent  
Office

# PARTIAL EUROPEAN SEARCH REPORT

Application Number

which under Rule 45 of the European Patent Convention EP 98 89 0309 shall be considered, for the purposes of subsequent proceedings, as the European search report

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 398 861 A (GREEN) 21 March 1995 * figures 4-8 *	1,2,4,5	A61B17/064
X	EP 0 513 736 A (USSC) 19 November 1992 * figure 1 *	1-3,5	
X	EP 0 432 320 A (OBERLANDER) 19 June 1991 * figure 1 *	1,5	
X	EP 0 534 152 A (USSC) 31 March 1993 * figure 12 *	1,5	
A	US 3 800 783 A (JAMSHIDI) 2 April 1974 * figure 4 *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			A61B
INCOMPLETE SEARCH			
<p>The Search Division considers that the present application, or one or more of its claims, does/do not comply with the EPC to such an extent that a meaningful search into the state of the art cannot be carried out, or can only be carried out partially, for these claims.</p> <p>Claims searched completely :</p> <p>Claims searched incompletely :</p> <p>Claims not searched :</p> <p>1</p> <p>Reason for the limitation of the search:</p> <p>Article 52 (4) EPC - Method for treatment of the human or animal body by surgery</p>			
Place of search		Date of completion of the search	Examiner
THE HAGUE		1 February 1999	Barton, S
CATEGORY OF CITED DOCUMENTS			
<p>X : particularly relevant if taken alone</p> <p>Y : particularly relevant if combined with another document of the same category</p> <p>A : technological background</p> <p>O : non-written disclosure</p> <p>P : intermediate document</p> <p>T : theory or principle underlying the invention</p> <p>E : earlier patent document, but published on, or after the filing date</p> <p>D : document cited in the application</p> <p>L : document cited for other reasons</p> <p>&amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P4/C07)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 89 0309

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-02-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5398861	A	21-03-1995	NONE	
EP 513736	A	19-11-1992	US 5269783 A	14-12-1993
			CA 2066914 A	14-11-1992
			DE 69201400 T	13-07-1995
			US 5374268 A	20-12-1994
			US 5643319 A	01-07-1997
EP 432320	A	19-06-1991	CA 2004658 A,C	05-06-1991
			US 4997436 A	05-03-1991
			US 5002562 A	26-03-1991
			US 5154189 A	13-10-1992
EP 534152	A	31-03-1993	CA 2078982 A	27-03-1993
			DE 69215053 D	12-12-1996
			DE 69215053 T	03-04-1997
			US 5354305 A	11-10-1994
US 3800783	A	02-04-1974	GB 1393068 A	07-05-1975

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82